



N30H

N30H-Tri-Colour Digital Meter

Product Code	N30H-	X	X	XX	XX	X	X
Supply	85 ... 253 V AC (40 ... 400 Hz); 90 ...320 V DC	1					
	20...40 V AC (40 ... 400 Hz); 20...60 V DC	2					
Additional Outputs	Lack		0				
	OC Output, RS485 (Port 2), Analog Output		1				
	OC Output, RS485 (Port 2), Analog Output, Switched -Over Relay Outputs		2				
Unit	Unit Code Acc. to the Table - 1			XX			
Version	Standard				00		
	Custom-Made*				XX		
Language	English					U	
	Other*					X	
Acceptance Tests	Without Extra Requirements						0
	With an Extra Quality Inspection Certificate						1
	According to Customer's Request*						X



Table for N30H-

Unit	Code	Unit	Code	Unit	Code	Unit	Code	Unit	Code	Unit	Code	Unit	Code
Lack of Unit	00	MW	09	kvarh	18	° F	27	s	36	obr/min	45	m ³ /h	54
V	01	var	10	Mvarh	19	K	28	h	37	rpm	46	kg/h	55
A	02	kvar	11	kVAh	20	%	29	m ³	38	mm/min	47	l/h	56
mV	03	Mvar	12	MVAh	21	%RH	30	obr	39	m/min	48	On Order ¹	XX
kV	04	VA	13	Hz	22	pH	31	szt	40	l/min	49		
mA	05	kVA	14	kHz	23	kg	32	imp	41	m ³ /min	50		
kA	06	MVA	15	W	24	bar	33	rps	42	szt/h	51		
W	07	kWh	16	kW	25	m	34	m/s	43	m/h	52		
kW	08	MWh	17	° C	26	l	35	l/s	44	km/h	53		
1) After agreeing with the manufacturer													

Commonly Used Ranges for N30H

N30H 100000U0	Inp: Prg; Aux: 85-253VAC/DC; O/P: Lack
N30H 110000U0	Inp: Prg; Aux: 85-253VAC/DC; O/P: RS485, Analog, OC
N30H 120000U0	Inp: Prg; Aux: 85-253VAC/DC; O/P: RS485, Analog, OC, 2x Relay