



**Part Number
Coding Booklet**

Theta Series - P30U

P30U- Transducer of Temperature, DC Current & Voltage

Product Code	P30U-	X	X	X	X	XX	X	X
Analog Output	Current: 0/ 4 ... 20 mA	1						
	Voltage: 0 ... 10 V	2						
SD/ SDHC Card	No Service		0					
	With Service		1					
Addition Output	Relay (NO Type - 250V AC, 5A 30V DC)			1				
	Supply 24 V DC/ 30 mA			2				
Supply	85 ... 253 V AC/ DC				1			
	20 ... 40 V AC, 20 ... 60 V DC				2			
Version	Standard					00		
	Custom-Made *					XX		
Language Version	English						U	
	Other						X	
Acceptance Tests	Without Extra Requirements							0
	With An Extra Quality Inspection Certificate							1
	According to Customer's Request							X

* After Agreeing with manufacturer.

Commonly Used Ranges for P30U-

P30U 101100U0	Inp: Uni; Analog O/P: 4-20mA; Addl Equip: Lack; Addl. O/P: Relay; Aux: 85-253VAC/DC
P30U 111100U0	Inp: Uni; Analog O/P: 4-20mA; Addl Equip: SD Card Slot; Addl. O/P: Relay; Aux: 85-253VAC/DC
P30U 121100U0	Inp: Uni; Analog O/P: 4-20mA; Addl Equip: Internal Mem with Eth Port; Addl. O/P: Relay; Aux: 85 253VAC/DC



Email: psk@sifamtinsley.com | Web: www.sifamtinsley.com

Phone: 404.736.4903 | Fax: +1 678 881 0008 x 701 | Toll Free: 800 879 6171

3105 Creekside Village Dr, Unit 801, Kennesaw GA 30144