



**Part Number
Coding Booklet**

Theta Series - TT40

Theta 40- Multifunction Transducer

Product Code	TT40-	X	X	XXXXXXXXXX
Product Type	M42	1	F	
	M24	2		
	M20	3		
	M40 RS 485	4		
	M30	5		
	M01 RS 485	6		
	M00 LONBUS	7		
Power Supply	24-60V AC/DC		J	
	85-230V AC/DC			
Version	Standard			0000000000

Commonly Used Ranges for Theta 40-

TT40-1F0000000000	Multi transducer: M42 Aux: 24-60VACDC; 4 Analog; 2 Digital; RS232 Interface
TT40-1J0000000000	Multi transducer: M42 Aux: 85-230VACDC; 4 Analog; 2 Digital; RS232 Interface
TT40-2F0000000000	Multi transducer: M24 Aux: 24-60VACDC; 2 Analog; 4 Digital; RS232 Interface
TT40-2J0000000000	Multi transducer: M24 Aux: 85-230VACDC; 2 Analog; 4 Digital; RS232 Interface
TT40-3J0000000000	Multi transducer: M20 Aux: 85-230VACDC; 2 Analog Outputs; RS 232 Interface
TT40-5J0000000000	Multi transducer: M30 Aux: 85-230VACDC; 3 Analog Outputs; RS 232 Interface
TT40-4J0000000000	Multi transducer: M40 RS485 Aux: 85-230VACDC; 4 Analog Outputs; RS 485 Interface
TT40-4F0000000000	Multi transducer: M40 RS485 Aux: 24-60VACDC; 4 Analog Outputs; RS 485 Interface



Email: psk@sifamtinsley.com | Web: www.sifamtinsley.com

Phone: 404.736.4903 | Fax: +1 678 881 0008 x 701 | Toll Free: 800 879 6171

3105 Creekside Village Dr, Unit 801, Kennesaw GA 30144