

Multifunction Meters

Transducers & Isolators

Temperature Controllers

Converters & Recorders

Digital Panel Meters

Current Transformers

Analogue Panel Meters

Shunts

Digital Multimeters

Clamp Meters

Insulation Testers

LTRC SERIES - RESIN CAST CURRENT TRANSFORMER

User Manual - Issue 1.0



Features

- → Compact size
- → Wide range of system current Ratings
- → Transparent terminal cover
- → Wall mounting.
- → Terminal with self lifting screw

General Specification


Applicable standard:	IEC61869-1 & 2
Case:	Epoxy Resin
Insulation class:	E(120°C max)
Test voltage:	3KV 50 Hz for 1 minute
Operating frequency:	50Hz
Rated Primary current:	100A to 1200A
Rated secondary current:	5A standard
Continuous current:	1.2X Rated current
Rated system voltage:	0.72/3KV
Ambient temperature range:	25 to +40°C
Storage temperature range:	50 to +80°C

LTRC-1 Series

LTRC-180/30(50)



LTRC-1 80/30(50)				
LTRC-100/30(30)				
Ratio	VA	Class		
100	5	1		
125	5	1		
150	5	1		






LTRC-2 Series

LTRC-2 90/50(40)






LTRC-2 90/50(40)			
Ratio	VA	Class	
200	10	1	
250	10	1	
300	10	1	

LTRC-3 Series

LTRC-3 110/72(40)



LTRC-3 110/72(40)				
Ratio	VA	Class		
400	15	1		
500	15	1		
600	15	1		
630	15	1		






LTRC-4 Series

LTRC-4 135/85(40)





LTRC-4 135/85(40)				
Ratio	VA	Class		
800	15	1		
1000	15	1		
1200	15	1		

Sifam Tinsley Instrumentation Inc.