

Delta Clip B

Delta Clip B for AC current measurement



Operating Manual

Application:

The Delta Clip B (300 A / 1000 A) measures current without interrupting the conducting line. They are used for electrically isolated measurement of alternating current within a broad range, without interrupting the current conducting cable and bus bars.

Features of Delta Clip B:

- * Safety in accordance with IEC 61010-1.
- * Minimum transformation ratio error.
- * Compact, handy design.
- * Permanently connected safety cables.

Safety Features & Precautions:



- Application around & removal from HAZARDOUS LIVE conductor is permitted

The delta clip current transformers are constructed with safety rules of IEC 61010-1. When in operation the safety of user and unit is assured. Also when the secondary circuit is interrupted, the Clamp has a Protection circuit which prevents high voltage to be generated. Before operating read completely the instruction manual. These instruction must be followed by users in all respects. In case of incorrect use or careless handling, the safety of both user and clamp is not assured.

Measurement:

The Delta Clip B measures AC current without interrupting the conducting line. opening contact of both the core which become visible when trigger is pressed, must be always kept clean. Even small outside particles can deviate measuring accuracy. The measuring secondary long cables with contact-protected connection plugs, which electrically isolates the measurement of AC current without interruption.



Delta Clip B

The Delta Clip B 300A should be used as accessories for Multi 12s which directly displays the Current in 300A range.



Delta Clip B

The Delta Clip B 1000A should be used as accessories for Multi series.

Periodic Check-up :

The Delta Clip B does not require any specific maintenance. While cleaning, the probes must not be immersed into any liquid. No special maintenance is required for housing. The surface between the opening jaws should be cleaned with dry cloth before operating. Avoid use of cleansers, abrasives or solvents.

Specifications :

Delta Clip B		
Type	CT 1000A	CT 300A
Description/ Application	The current transformers are used for electrically isolated measurement of alternating current within broad range. It is possible to measure AC current without interrupting the current conducting cable and bus bars via hard wired leads with contact protected plugs.	
Nominal Primary Current	1-1000 A AC	4-300 A AC
Output signal	1mA AC / A AC	0.3 mA AC / A AC
Used with	Multi series	Multi 12s
Transmission ratio Input:Output	1000:1	1000:1
Accuracy / max. error	Class 1 (2.5 VA) (for current range from 1A to 1000A, 50Hz)	Class 1 (1.25 VA) (for current range from 4A to 300A, 50Hz)
Max. operating Voltage	CAT III 600 V as per IEC-61010	CAT III 600 V as per IEC-61010
Frequency range	40Hz....1kHz	40Hz....1kHz
Jaw opening / Conductor Diameter	43mm / Diameter 43mm	35mm / Diameter 35mm
Dimensions (W X H X D)	(92 X 39 X 220) mm	(84 X 39 X 202) mm
Weight	Approx 650 gms	Approx 500 gms
Cable length	1.5 meter	1.5 meter



sifam tinsley
PRECISION INSTRUMENTATION

Sifam Tinsley Instrumentation
3105, Creekside Village Drive,
Suite No 801, Kennesaw,
Georgia 30144
Contact Number: +1.404.736.4903
Web: www.sifamtinsley.com

Sifam Tinsley Instrumentation Ltd.
Central Buildings, Woodland Close,
Old Woods Trading Estate,
Torquay, Devon, England, TQ27BB
Website: www.sifamtinsley.com/uk
Contact Number: +44(O) 1803 615139
E-mail: info@tinsley.co.uk

Subject to change without notice
Item Code : 2-60-006-00-00566
Revision - C
Printed In India