



**Part Number
Coding Booklet
Theta Series - P43**

P43-Transducer of 3-Phase Power Network Parameters

Product Code	P43-	X	X	X	XX	X
Current Input (In)	1 A (X/ 1)	1	1	1	00	8
	5 A (X/ 5)	2				
Voltage Input (Phase/ Phase - to - Phase) Un	3 x 57.7/ 100 V		1	1	00	8
	3 x 230/ 400 V		2			
Supply Voltage	85 ... 253 V AC/ DC			1	00	8
	20 ... 40 V AC/ DC			2		
Kind of Execution	Standard				00	8
	Custom-Made				XX	
Acceptance Tests	Without Extra Quality Requirements					8
	With an Extra Quality Inspection Certificate					7
	Acc. to Customer's Requirements*					X

Commonly used Ranges for P43-

P43 111200U0	Inp: 1A & 100V AC; Aux: 85-253VAC/DC; O/P: 2x Analog & 2x Relay
P43 211200U0	Inp: 5A & 100V AC; Aux: 85-253VAC/DC; O/P: 2x Analog & 2x Relay
P43 111300U0	Inp: 1A & 100V AC; Aux: 85-253VAC/DC; O/P: 4x Analog
P43 211300U0	Inp: 5A & 100V AC; Aux: 85-253VAC/DC; O/P: 4x Analog



Email: psk@sifamtinsley.com | Web: www.sifamtinsley.com

Phone: 404.736.4903 | Fax: +1 678 881 0008 x 701 | Toll Free: 800 879 6171

3105 Creekside Village Dr, Unit 801, Kennesaw GA 30144